

RECEIPT/LABEL



LOGISTICS



TRANSPORTATION



WAREHOUSE MANAGEMENT



HOSPITAL



DELIVERY



DRUGSTORE

RECEIPT



FOOD DELIVERY



RESTAURANT



BUS/TAXI RECEIPT



TRAFFIC CITATION

AlfaPrinter P43 Portable Printer

- Receipt/Label Printer
- Compact and rugged design
- Peel-off function(Optional)
- IP54 Certified : protection against dust and water
- Large capacity of paper roll up to 56mm(OD)
- Adjustable paper width from 50 to 112mm
- Flexible connectivity including RS-232C, USB, Bluetooth or Wi-Fi(802.11 a/b/g)
- Prints at 80mm per second
- Fast AC charger and long life battery
- Color Graphic LCD 128x64 dots



AlfaPrinter P43

PRINTING SPECIFICATION

PRINTING

METHOD : Direct Thermal
SPEED : 80mm/sec
WIDTH : 104 mm (4.1")
RESOLUTION : 203 DPI (8 dots/mm)

BARCODE

1D : EAN-8, EAN-13, EAN-128, RSS, Postnet, Code39, Code93, Code128, Codabar, ITF, UPC-A, UPC-E
2D : PDF417, QR Code, Maxicode, GS-1, Datamatrix, Aztec

PAPER/MEDIA SPECIFICATION

PAPER

TYPE : Thermal receipt / label
WIDTH : 50 ~ 112mm
ROLL DIAMETER : Max. Ø 56mm

HARDWARE SPECIFICATION

BATTERY CHARGER

AC/DC Charger

BATTERY

7.4V / 2600mAh, 5200mAh

SENSOR

STARNDARD : Paper End, Gap, Black Mark, Cover Open

TEMPERATURE

OPERATING TEMPERATURE : -21 ~ 55°C
STORAGE TEMPERATURE : -30 ~ 65°C

HUMIDITY

OPERATING HUMIDITY : 10 ~ 90%
STORAGE HUMIDITY : 10 ~ 90%

DROP RESISTANCE

1.8M(standard)

IP

IP54 certified

LCD

Color graphic LCD 128 x 64 dots

INTERFACE

INTERFACE

STANDARD : Serial(RS-232C), USB
OPTION : Buletooth Class 2, Wi-Fi(802.11 a/b/g)

SOFTWARE

EMULATION

ESC/POS, CPCL, ZPL Command compatible

DIMENSION SPECIFICATION

DIMENSION

W x D x H(mm) : 154x174x80 (mm)
W x D x H(inch) : 6x6.8x3.1(inch)

WEIGHT

1kg (with 2600mAh battery)

OPTION

PEELER



PRODUCT FEATURES

PAPER INPUT WINDOW



CONTROL PANEL USAGE

